

# Sapa Facade 4150 PH

Instructions.

Isolated glazed facade in aluminium Sapa Facade 4150 PH.  
Watertightness class RE1200 acc. to EN 12154.  
Air permeability class A<sub>4</sub> acc. to EN 12152.  
Max. U-value for the whole facade:  
Sound insulation: Rw/ Rw+Ctr.  
Facade performed as partition between slabs/ curtain wall.  
Profile width 50mm. Profile depth dimensioned by facade supplier.  
Decorating profiles vertically.  
Decorating profiles horizontally.  
Surface treatment anodizing nature/ HX 5/ HX 10/ HX 20/ HX 30/ HX 40/ HX 50.  
Surface treatment powder coating 60 µm, pretreatment acc. to Sapa std. Color NCS S/ RAL.  
Triple glass/ toughened/ laminated/ sunscreen.  
Infill panels with cladding glass/ al-sheet on moisture resistant board.  
Inside finishes on infill panels interior board/ al-sheet.  
Installation and connections acc. to Sapa instructions.

Select U-value.  
Select type and dB.  
Select alternative.  
Profile depth min 120 mm  
Select profile.  
Select profile.  
Select one type.  
Select color.  
Select alternative. Glass thickness 48-56mm.  
Select alternative.  
Select alternative.