

Sapa Door 2050

Fire resistant

Instructions.

Unisolated doorpart in aluminium Sapa Door 2050.
Profile depth 50 mm.
Fire-resistance grade E 30.
Outward opening/ inward opening, single door/ double door.
Narrow section/ modular section.
Rebate seal/ wool pile/ strip seal/ without threshold.
Surface treatment anodizing nature/ HX 10/ HX 20/ HX 30/ HX 40/ HX 50.
Surface treatment powder coating 60 µm, pretreatment acc. to Sapa std. Color NCS S/ RAL.
Approved glass acc. to Sapa, single glass/ double glass.
Approved infill panel acc. to Sapa.
Approved hinges acc. to Sapa.
Door handle.
Approved lock.
Approved lock striker.
Approved electric strikes.
Wiring loop.
Approved door closing device.
Approved automatic door opening device.
Panic or emergency device.
Flushbolt, single action/ double action acc. to Sapa std.
Automatic flushbolt acc. to Sapa std.
Door coordinator.
Installation and connections acc. to Sapa instructions.

Select alternative.

Select one alternative.

Select alternative.

Select one type.

Select color.

Select alternative. Glass thickness max 34mm.

Select finishes.

Select type.

Select type.

Select type and function.

Select type.

Select type.

Select type.

Select type.

With double door.

With double door.

Select type. With double door.