

Sapa Glazed Roof 5050

Instructions.

Isolated glazed roof in aluminium Sapa Glazed roof 5050.
Watertightness class R7 acc. to EN 12154.
Air permeability class A4 acc. to EN 12152.
Max. U-value for the whole roof.
Sound insulation: Rw/ Rw+Ctr.
Roof performed as monopitch roof/ ridged roof/cantilever ridged roof.
Slope.
Profile width 50mm. Profile depth dimensioned by roof supplier.
Decorating profiles vertically.
Decorating profiles horizontally.
Surface treatment anodizing nature/ HX 10/ HX 20/ HX 30/ HX 40/ HX 50.
Surface treatment powder coating 60 μm , pretreatment acc. to Sapa std. Color NCS S/ RAL.
Double/ triple glass with inside glass laminated and the outside glass toughened.
Sun protection in the glass/ arranged on the inside/ outside of the glazed roof.
Outward opening shutters for smoke ventilation/ comfort ventilation.
Service ladders and service carriages for maintenance.
Installation and connections acc. to Sapa instructions.

Select U-value.

Select type and dB.

Select alternative.

Select slope.

Select profile or no profile.

Select profile or no profile.

Select one type.

Select color.

Glass thickness 24-35, 44-51mm.

Select alternative and type.

Select alternative and opening function.

Investigated.