




							
	Min.		Max.		alternativ bågprofil			
	B	H	B	H	B	H	B	H
Sidohängt LM 4200 	498	548	1448	1948	1648	2048	1648	2048
			Max bågvt 100 kg Max B+H = 2650 mm Max B = 1,5 x H	Max bågvt 115 kg Max B+H = 3150 mm Max B = 1,5 x H	Max bågvt 130 kg Max B+H = 3750 mm Max B = 1,5 x H			
Undersidohängt LM 4200-TBT 	498	598	1448	1948	1648	2048	1648	2048
			Max bågvt 100 kg Max B+H = 2650 mm Max B = 1,5 x H	Max bågvt 115 kg Max B+H = 3150 mm Max B = 1,5 x H	Max bågvt 130 kg Max B+H = 3750 mm Max B = 1,5 x H			
Underhängt LM-K/ZV 	583	548	1448	1948	1648	2048	1648	2048
			Max bågvt 100 kg Max B+H = 2650 mm	Max bågvt 100 kg Max B+H = 3150 mm	Max bågvt 100 kg Max B+H = 3750 mm			
Underhängt LM-K 	448	498	1948	1248	2298	1248	2448	1248
			Max bågvt 50 kg	Max bågvt 50 kg	Max bågvt 50 kg			
Överhängt LM-K 	568	498	1448	848	2048	848	2448	848
			Max bågvt 50 kg	Max bågvt 50 kg	Max bågvt 50 kg			